

Analytical HPLC

LC-4000 Series



JASCO

Performance
Innovation
Reliability

The LC-4000 Series HPLC is the latest in a long history of innovative HPLC systems developed by JASCO reaching all the way back to the start of the commercial HPLC in the early 1970s.

The concept of the integrated LC-4000 series HPLC provides key separation platforms at 300bar, 700bar and 1300bar which correspond to conventional HPLC, the increasingly popular Rapid Analysis (RHPLC) and sub 2 μ m UHPLC, respectively. Each platform is supplied with a dedicated pump and autosampler matched to the operating pressure and all three platforms share common detectors optimized for high-speed 100 Hz acquisition and narrow peak shapes common to both RHPLC and UHPLC.


Table of contents

System	
LC-4000 Advances	3
System Configurations	4
Detector Options	5
Software	
ChromNAV	6
Specifications	8


LC-4000 Advances

Flow Innovation


For over two decades JASCO analytical HPLC pumps have employed an asymmetric twin-piston delivery system SSQD (Slow Suction, Quick Delivery) providing significantly better flow and pressure profiles than conventional twin-piston reciprocating designs. The SSQD was redeveloped for the LC-4000 series to offer the highest stability in solvent delivery using ExReFT (Extremely Reliable Flow Technology).



Retention Time	Naphthalene	Fluorene	Anthracene	Pyrene	Chrysene	Benzo[a]pyrene
% RSD	0.025	0.018	0.017	0.022	0.016	0.020



Redesigned flow cells for excellent peak shape.



Pioneering Optical Design

As a pioneer in optical spectroscopy dating back over 65 years, JASCO has been at the forefront of optical detection. Adapting designs from the most powerful spectrometers, JASCO has developed a range of HPLC detectors with unrivalled performance like the class leading FP-4020 fluorescence detector with S/N of over 2300:1 and the world's only circular dichroism detector for chiral chromatography. Dual simultaneous wavelength detection is offered as standard on the UV and FP detectors adding flexibility and versatility. In addition, JASCO offers RI (refractive index), PDA, OR (optical rotation), and MS detectors.

Compact and Easy to Use

Despite the extra power delivered by the LC-4000 series HPLC, the standard footprint is only 300mm wide requiring very little bench space. For those users that require front panel control, the LC-4000 series returns the popular keypad and display.

For easy user maintenance, all LC-4000 modules feature front access for replacing consumables such as check valves and seals in the pumps, sample needle and syringe parts in the autosamplers and lamps for the detectors.



Configurations

HPLC

Designed for routine HPLC research and academic settings.
For use with 5 μ m columns.

Flow rate: 0.5 - 10.0 mL/min (Semi-Micro option 0.05-4mL/min)
Pressure: Analytical 350 bar : 0.5 - 10 mL/min
Semi-micro 400 bar : 0.05-4mL/min
Inert 250 bar

Options:

- Isocratic
- High Pressure Gradient
- Low Pressure Gradient
- Autosampler up to 100 μ L injections standard
Optional 1ml injection and temperature control
- Column Oven for various column lengths
- UV, PDA, FP, RI, CD, OR, MS

RHPLC

Designed for those requiring more sample throughput. For use with 2.5 μ m coreshell, 3 μ m and 5 μ m columns.

Flow rate: 0.5 - 6.0 mL/min (Semi-Micro option 0.05-3mL/min)
Pressure: 700bar

Options:

- Isocratic
- High Pressure Gradient
- Low Pressure Gradient
- Autosampler up to 20 μ L injections standard
Optional 1ml injection and temperature control
- Column Oven for various column lengths
- Detection: UV, PDA, FP, RI, CD, OR, MS

UHPLC

Designed for those requiring the highest sample throughput. For use with sub-2 columns.

Flow rate: 0.05 - 1.5 mL/min
Pressure: 1000 bar : 0.05-2.0
1300 bar : 0.05-1.5

Options:

- Isocratic
- High Pressure Gradient
- Autosampler up to 5 μ L injections standard
Optional 1ml injection and temperature control
- Column Oven for various column lengths
- Detection: UV, PDA, FP, RI, CD, OR, MS



Detectors



UV-4070/4075 UV-Visible Detector

Both detectors offer simultaneous dual wavelength acquisition and spectra scanning.

Wavelength ranges:
UV 4070: 190-900nm
UV 4075: 190-600nm



MD-4010/4015/4017 UV-Visible PDA Detectors

When 2 wavelengths are not enough a PDA can provide the additional needed as well as spectral information and identification possibilities.

Wavelength ranges:
MD-4010: 190-900nm
MD-4015: 200-600nm
MD-4017: 200-400nm



CD-4095 Circular Dichroism Detector

The world's only circular dichroism detector that provides the utmost sensitivity.

Wavelength range:
220-460nm



CMS Mass Spectrometer

When mass identification is needed the CMS offers ESI, APCI or ASAP with positive and negative switching.

CMS-S up to 1200 m/z
CMS-L up to 2000 m/z



FP-4020/4025 Fluorescence Detector

For the ultimate in sensitivity the FP-4020 provides S/N of 2300:1. The FP-4025 offers excellent sensitivity with S/N of 1400:1 and both offer simultaneous detection of 2 wavelength pairs.

Wavelength range: 200-700nm



OR-4090 Optical Rotation Detector

The optical rotation detector provides chiral detection for optically active isomers and chiral compounds that have no absorption.

Wavelength ranges:
350-900nm
Light source: Hg/Xe lamp



RI-4030/4035 Refractive Index Detector

The refractive index detector is a universal detector for those compounds that cannot be seen on the UV or FP.

RI-4030 up to 120mL/min
RI-4035 for RHPLC/UHPLC

Related Instruments



LCMS



Prep LCMS


ChromNAV Software

ChromNAV 2.0 (and ChromNAV-CFR 2.0) are JASCO's next generation CDS developed from the powerful and easy-to-use ChromNAV 1.0 with a host of existing new features. With a customizable graphical-user-interface (GUI), the user can set-up the system to display only the functions necessary for their application. This latest intuitive GUI allows the user to quickly learn the operation and explore the extensive functionality of data processing.

ChromNAV 2.0 is a universal CDS which can be used with any type of separation – HPLC, RHPLC, UHPLC, Prep LC, Analytical SFC and Prep SFC. ChromNAV can also satisfy the demands of dedicated analyses or multi-purpose systems.


Control Method

The pump flow rate and gradient profile display is flexible and can be overlaid with a chromatogram for adjusting gradient conditions.



PDA Analysis

PDA data processing is included as standard. Data is displayed in a 2D contour plot and 3D with simultaneous overlay of spectra and chromatograms. Chromatograms can be extracted at single or multiple wavelengths for quantitation.



ChromNAV 2.0 offers powerful system control and data acquisition. During acquisition, the run-time can be extended to capture later eluting peaks. Previously acquired chromatograms can be overlaid for visual comparison with data currently being acquired.

Samples can be changed or added to the sequence while it is acquiring. Also the sequence can be setup to stop the pump, turn off the lamps, turn of the oven temperature and even turn off the power on the system at the end of the sequence.

Specifications

Pumps

Isocratic

System	HPLC	RHPLC	UHPLC
Flow Range	0.5 - 10.0 mL/min Semi-micro 0.05 - 4.0 mL/min	0.05 - 10.0 mL/min Semi-micro 0.05 - 4.0 mL/min	0.05 ~ 1.5 mL/min (130MPa) ~ 2.0 mL/min (100MPa)
Maximum Pressure	300 bar	700 bar	1300 bar
Flow Rate Accuracy	±1% or ± 2µl/min		
Flow Rate Precision <i>Measured by Chromatogram</i>	0.05% RSD or ±0.04min SD		
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 13kg		300 (W) x 470 (D) x 150 (H) mm, 14.5kg
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 80 VA		AC 100 ~ 240 V, 50/60 Hz, 60 VA

Low Pressure Gradient

System	HPLC	RHPLC	UHPLC
Mixing Accuracy	± 0.8% (5~95%, 0.5 ~ 5.0mL/min)	± 0.6% (5~95%, 0.2 ~ 1.0mL/min) ± 1.2% (5~95%, ~ 4.0mL/min)	N/A
Mixing Precision <i>Measured by Chromatogram</i>	0.25% RSD or ±0.02min SD	0.15% RSD or ±0.01min SD	
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 19.5kg		300 (W) x 470 (D) x 150 (H) mm, 22.5kg
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 130 VA		AC 100 ~ 240 V, 50/60 Hz, 100 VA

Binary High Pressure Gradient

System	HPLC	RHPLC	UHPLC
Mixing Accuracy	± 0.4% (5-95%, 0.5 - 10.0mL/min)	± 0.4% (5-95%, 0.2 - 4.0mL/min)	± 0.4% (5-95%, 0.2 - 2.0mL/min)
Mixing Precision <i>Measured by Chromatogram</i>	0.15% RSD or ±0.01min SD		
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 19.5kg		300 (W) x 470 (D) x 150 (H) mm, 22.5kg
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 130 VA		AC 100 ~ 240 V, 50/60 Hz, 100 VA

Autosamplers

Model	AS-4050 (HPLC)	AS-4150 (HPLC/RHPLC)	AS-4250 (UHPLC)
Sample Injection Method	Full or partial fill loop injection		
Number of Samples	60 (2 mL vials)	180 (2 mL vials)	
Injection Volume	0.1~ 100 μ L Large volume option (1~1000 μ L)		
Injection Accuracy	\pm 0.1% or less		
Injection Precision	0.3% RSD or less	0.25% RSD or less	
Carry Over	0.01% or less	0.01% or less 0.005% or less with multiple solvent flushing	
Maximum pressure	30 MPa	70 MPa	130 MPa
Sample Cooling/ Heating	Option: 4 ~ 40°C		
Pre-Column Derivatization	Yes, up to 2 reagents, dilution, other user programs		
Dimensions, Weight	300 (W) x 470 (D) x 300 (H) mm, 21kg	300 (W) x 470 (D) x 385.5 (H) mm, 25kg	
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 60 VA	AC 100 ~ 240 V, 50/60 Hz, 75 VA	

Column Ovens

Model	CO-4061	CO-4062	CO-4060	CO-4065	RO-4061
Temperature Range	Ambient -15°C ~ 100°C		Ambient -15°C ~ 80°C	Ambient -15°C ~ 90°C	Ambient+10°C ~ 200°C
Column Compartment Dimensions	270 (W) x 30 (D) x 60 (H) mm Option 380 (W) mm	260 (W) x 25 (D) x 105 (H) mm	110 (W) x 105 (D) x 410 (H) mm	260 (W) x 120 (D) x 410 (H) mm	43 (W) x 354 (D) x 76 (H) mm
Safety Features	Heating/cooling power shut off when unusually high temperatures or solvent leaks are detected				
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 10kg		150 (W) x 470 (D) x 465 (H) mm, 16kg	300 (W) x 470 (D) x 465 (H) mm, 25kg	300 (W) x 470 (D) x 150 (H) mm, 12kg
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 160 VA	AC 100 ~ 240 V, 50/60 Hz, 200 VA	AC 100 ~ 240 V, 50/60 Hz, 350 VA	AC 100 ~ 240 V, 50/60 Hz, 660 VA	AC 100 ~ 240 V, 50/60 Hz, 450 VA

Specifications

Detectors

UV-Vis and Circular Dichroism

Model	UV-4070	UV-4075	CD-4095
Light Source	D2 lamp + Wl lamp	D2 lamp	Hg-Xe lamp
Wavelength Range	190 ~ 900 nm	190 ~ 600 nm	220 ~ 460 nm
Noise Level	$\pm 0.2 \times 10^{-5}$ AU (specified condition)		0.04 mdeg (at specified conditions)
Drift <i>At constant room temperature</i>	$\pm 1 \times 10^{-4}$ AU/h (specified condition)		0.1mdeg/h (at specified conditions)
Data Output	100 Hz		
Flow Cell	Temperature controlled, tapered, path length 10 mm		Tapered cell, path length 25 mm
Spectrum Measurement	200 ~ 900 nm	200 ~ 600 nm	220 ~ 460 nm
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 14kg		300 (W) x 470 (D) x 225 (H) mm, 21kg
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 175 VA	AC 100 ~ 240 V, 50/60 Hz, 125 VA	AC 100 ~ 240 V, 50/60 Hz, 210 VA

Photo Diode Array

Model	MD-4010	MD-4015	MD-4017
Light Source	D2 lamp + Wl lamp	D2 lamp	D2 lamp
Wavelength Range	190 ~ 900 nm	200 ~ 600 nm	200 ~ 400 nm
PDA Elements	1024 ch	512 ch	512 ch
Slit Width	1, 4, 8 nm	4 nm	4 nm
Noise Level	$\pm 3.0 \times 10^{-6}$ AU (specified condition)		$\pm 7.0 \times 10^{-6}$ AU (specified condition)
Drift	$<0.5 \times 10^{-3}$ AU/h (specified condition)		$<1.0 \times 10^{-3}$ AU/h (specified condition)
Linearity	2.0 AU or more (specified condition)		
Data Acquisition Rate	100 spectra/sec		20 spectra/sec
Flow Cell	Path length 10 mm		
PC Communication	USB		
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 14.5kg	300 (W) x 470 (D) x 150 (H) mm, 13.5kg	
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 180 VA	AC 100 ~ 240 V, 50/60 Hz, 150 VA	AC 100 ~ 240 V, 50/60 Hz, 120 VA

Fluorescence

Model	FP-4020	FP-4025
Light Source	Xenon short arc lamp	
Wavelength Range	200 ~ 700 nm Option up to 900nm	
Spectral Bandwidth	EX: 20nm, EM: 20 or 40nm	
Sensitivity	Raman peak of water S/N > 2300	Raman peak of water S/N > 1400
Data Output	100 Hz	
Flow Cell	Front loading cassette cell	
Temperature Control	OFF, ambient -10°C ~ 40°C	-
Spectrum Measurement	Excitation and emission spectrum measurement	
Two-Wavelength Monitoring	Two sets of Ex/Em wavelength setting. Maximum wavelength difference 200nm or shorter.	
Dimensions, Weight	300 (W) x 470 (D) x 225 (H) mm, 24kg	
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 270 VA	AC 100 ~ 240 V, 50/60 Hz, 230 VA

Refractive Index

Model	RI-4030	RI-4035
Measurement System	Deflection type	
Refractive Index Range	5.0 x 10 ⁻⁵ RIU (HIGH) 5.0 x 10 ⁻⁴ RIU (STD) 5.0 x 10 ⁻³ RIU (LOW)(H ₂ O)	5.0 x 10 ⁻⁵ RIU (HIGH) 5.0 x 10 ⁻⁴ RIU (STD)(H ₂ O)
Noise Level	0.20 x 10 ⁻⁸ RIU or less (HIGH, STD)	0.50 x 10 ⁻⁸ RIU or less (HIGH, STD)
Cell Capacity	10 µL	2.7 µL
Maximum Flow Range	10 mL/min (Low flow tubing) 120 mL/min (High flow tubing)	1.2 mL/min (H ₂ O)
Maximum Pressure	0.1 MPa (Low flow tubing) 0.3 MPa (High flow tubing)	0.1 MPa
Temperature Control	Ambient + 10°C ~ ambient + 25°C	
Dimensions, Weight	300 (W) x 470 (D) x 150 (H) mm, 15kg	
Power Requirement	AC 100 ~ 240 V, 50/60 Hz, 80 VA	

ChromNAV 2.0

Language	English or Japanese
Windows OS	Windows 7 Professional 32/64 bit Windows 8.1 Professional 32/64 bit Windows 10 Professional 32/64 bit
Controllable Hardware	LC-4000, XLC-3000, LC-2000, some LC-1500 and some LC-900. Control up to 4 systems.



JASCO INTERNATIONAL CO., LTD.

11-10, Myojin-cho 1-chome, Hachioji, Tokyo 192-0046, Japan
Tel: +81-42-649-3247 Fax: +81-42-649-3518 <http://www.jascointl.co.jp/english/>
Australia, Hong Kong, India, Indonesia, Korea, Malaysia, New Zealand,
Pakistan, Philippines, Russia, Singapore, Taiwan, Thailand, Vietnam

JASCO INCORPORATED

28600 Mary's Court, Easton, Maryland 21601, U.S.A.
Tel: +1-410-822-1220 Fax: +1-410-822-7526 Web: www.jascoinc.com
Argentina, Bolivia, Brazil, Canada, Chile, Colombia, Costa Rica, Guatemala, Mexico,
Paraguay, Peru, Puerto Rico, United States of America, Uruguay, Venezuela

JASCO EUROPE S.R.L.

Via Luigi Cadorna 1, 23894 Cremella (LC), Italy
Tel: +39-039-9215811 Fax: +39-039-9215835 Web: www.jascoeurope.com
JASCO Deutschland www.jasco.de | **JASCO UK** www.jasco.co.uk | **JASCO France** www.jasco.fr
JASCO Benelux www.jasco.nl | **JASCO Spain** www.jasco-spain.com
Algeria, Austria, Belgium, Cyprus, Denmark, Egypt, Finland, France, Germany, Greece, Hungary, Iran, Iraq, Israel,
Italy, Jordan, Kuwait, Lebanon, Luxembourg, Morocco, Netherlands, Norway, Poland, Portugal, Romania, Saudi
Arabia, South Africa, Spain, Sweden Switzerland, Tunisia, Turkey, United Arab Emirates, United Kingdom, Yemen

JASCO China (Shanghai) Co., Ltd.

Room No.D, 10F, World Plaza, 855 Pudong South Road, Pudong New Area, Shanghai
Tel: +86-21-6888-7871 Fax: +86-21-6888-7879 <http://www.jasco-global.com>



Products described herein are
designed and manufactured by
ISO-9001 and ISO-14001-certified
JASCO Corporation